

CR 114 727

BOEING COMMERCIAL AIRPLANE COMPANY
A DIVISION OF THE BOEING COMPANY
SEATTLE, WASHINGTON

DOCUMENT NO. D6-41489

TITLE DESIGN OF A POWERED ELEVATOR CONTROL SYSTEM

FINAL REPORT

MODEL _____

ISSUE NO. _____ TO: _____ (DATE) _____

NASA Contract NAS 2-7293

PREPARED BY	<u>W.L.B. Glende</u>	<u>1/16/74</u>
SUPERVISED BY	<u>J.P. Headlund</u>	<u>1-21-74</u>
APPROVED BY	<u>R.H. Ashleman</u>	<u>1-22-74</u>
APPROVED BY	_____	_____
	_____	_____
	_____	_____
		(DATE)

LIST OF ACTIVE PAGES															
SECTION	PAGE NUMBER	REV SYM	ADDED PAGES					SECTION	PAGE NUMBER	REV SYM	ADDED PAGES				
			PAGE NUMBER	REV SYM	PAGE NUMBER	REV SYM	PAGE NUMBER				REV SYM	PAGE NUMBER	REV SYM	PAGE NUMBER	REV SYM
	1								50						
	2.1								51						
	2								52						
	3								53						
	4								54						
	5								55						
	6								56						
	7								57						
	8								58						
	9								59						
	10								60						
	11								61						
	12								62						
	13								63						
	14								64						
	15								65						
	16								66						
	17	A							67						
	18								68						
	19								69						
	20								70						
	21								71						
	22								72						
	23								73						
	24								74						
	25								75						
	26								76						
	27								77						
	28								78						
	29								79						
	30								80						
	31								81						
	32								82						
	33								83						
	34								84						
	35								85						
	36								86						
	37								87						
	38								88						
	39								89						
	40	A							90						
	41								91						
	42								92						
	43								93						
	44								94						
	45								95						
	46								96						
	47								97						
	48								98						
	49								99						

AD 12482

REV SYM

NO D6-41489
PAGE 2

7

LIST OF ACTIVE PAGES

SECTION	PAGE NUMBER	REV SYM	ADDED PAGES					SECTION	PAGE NUMBER	REV SYM	ADDED PAGES				
			PAGE NUMBER	REV SYM	PAGE NUMBER	REV SYM	PAGE NUMBER				PAGE NUMBER	REV SYM	PAGE NUMBER	REV SYM	PAGE NUMBER
	100														
	101														
	102														
	103														
	104														
	105														
	106														
	107														
	108														
	109														
	110														
	111														
	112														
	113														
	114														
	115														
	116														
	117														
	118														
	119														
	120														
	121														
	122														
	123														
	124														
	125														

D1 4100 7700 ORIG 3/71

REV SYM

BOEING

NO. D6-41489

PAGE 2.1



4-7000

REVISIONS

REV SYM	DESCRIPTION	DATE	APPROVAL

AD 1546 C

REV SYM

BOEING

NO. D6-41489

PAGE 3



5-7222

TABLE OF CONTENTS

	<u>Page</u>
TABLE OF CONTENTS	ii
1.0 SUMMARY	5
LIST OF ILLUSTRATIONS	7
NOMENCLATURE	10
2.0 INTRODUCTION	12
3.0 AIRPLANE DESCRIPTION	14
3.1 GENERAL FEATURES	14
3.2 SPRING TAB ELEVATOR CONTROL PROBLEM	15
3.3 EXTENT OF MODIFICATIONS	16
4.0 POWERED ELEVATOR SYSTEM DESIGN AND ANALYSIS	25
4.1 DESIGN REQUIREMENTS	25
4.2 DATA BASE	25
4.3 SYSTEM DESCRIPTION	27
4.4 PREDICTED LONGITUDINAL CONTROL CHARACTERISTICS	30
5.0 ENGINEERING GROUND TESTS	57
6.0 TAXI AND FLIGHT TESTS	80
7.0 CONCLUSIONS AND RECOMMENDATIONS	117
REFERENCES	118
APPENDIX 'A' - PILOT FLIGHT REPORT	119



1.0

SUMMARY

In October 1972, The Boeing Company was awarded a contract by NASA Ames Research Center that led to the design, fabrication and flight testing of a powered elevator system for the Augmentor Wing Jet STOL Research Aircraft (AWJSRA or Mod C-8A). The system replaces a manual spring tab elevator control system that was unsatisfactory in the STOL flight regime.

Pitch control on the AWJSRA is by means of a single elevator control surface. The elevator is used for both maneuver and trim control as the stabilizer is fixed. A fully powered, irreversible flight control system powered by dual hydraulic sources was designed. The existing control columns and single mechanical cable system of the AWJSRA have been retained as has been the basic elevator surface, except that the elevator spring tab is modified into a geared balance tab. The control surface is directly actuated by a dual tandem moving body actuator. Control signals are transmitted from the elevator aft quadrant to the actuator by a linkage system that includes a limited authority series servo actuator. Artificial feel forces are provided by a dualized feel system that schedules the feel gradient as a function of impact pressure. Trim control is obtained by shifting the neutral point of the feel system. Manual reversion control of the elevator is possible following the loss of both hydraulic systems.

The design was implemented on a government furnished C-8A tail assembly at Boeing, Seattle. The modified tail assembly was subsequently shipped to AMES RESEARCH CENTER for mating with the AWJSRA airframe. Following the functional and engineering ground tests, the AWJSRA was flight tested. The powered elevator control system has been demonstrated to be airworthy and to meet its design requirements. No adverse system characteristics were noted by the test pilots. Control problems encountered in the STOL flight regime with the spring tab elevator system were eliminated by the powered elevator installation.



Elevator deflection capability above 136 knots is higher than desirable due to lower-than-predicted hinge moments. This can produce tail loads in excess of design loads. The following recommendations are therefore made:

1. Pilots should be cautioned not to make large elevator inputs above 120 knots.
2. The powered elevator system should be flight tested with the actuator supply pressure reduced to 1500 psi. This change should be permanently incorporated if system performance is found acceptable.



LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Title</u>	<u>Page</u>
2.0-1	PROGRAM SCHEDULE	13
3.1-1	THREE-VIEW DRAWING OF MOD C-8A	18
3.1-2	LATERAL CONTROL SYSTEM	19
3.1-3	DIRECTIONAL CONTROL SYSTEM	20
3.1-4	SPRING TAB ELEVATOR CONTROL SYSTEM	21
3.2-1	FEEL CHARACTERISTICS - SPRING TAB ELEVATOR SYSTEM	22
3.2-2	ELEVATOR FLOAT ANGLE - SPRING TAB ELEVATOR SYSTEM	23
3.2-3	ELEVATOR DYNAMICS - SPRING TAB ELEVATOR SYSTEM	24
4.2-1	TAB - ELEVATOR EFFECTIVENESS RATIO	33
4.2-2	PREDICTED ELEVATOR HINGE MOMENT COEFFICIENT	34
4.2-3	ELEVATOR PER 'G' CHARACTERISTIC	35
4.3-1	ELEVATOR SURFACE CONFIGURATION	36
4.3-2	LONGITUDINAL CONTROL SYSTEM SCHEMATIC	37
4.3-3	CONTROL COLUMN INSTALLATION	38
4.3-4	CONTROL LINKAGE	39
4.3-5	ACTUATOR INSTALLATION	40
4.3-6	LINKAGE INSTALLATION	41
4.3-7	ACTUATOR SCHEMATIC	42
4.3-8	FEEL COMPUTER	43
4.3-9	FEEL CONTROL UNIT	44
4.3-10	TRIM TAB CONTROL SYSTEM	45
4.3-11	HYDRAULIC SYSTEM SCHEMATIC	46
4.4-1	PREDICTED ELEVATOR TO TRIM	47
4.4-2	PREDICTED ELEVATOR BLOWDOWN	48
4.4-3	PREDICTED FEEL FORCE CHARACTERISTICS	49
4.4-4	PREDICTED PCU OPERATING CHARACTERISTICS - DUAL HYD	50
4.4-5	PREDICTED PCU OPERATING CHARACTERISTICS - SINGLE HYD	51
4.4-6	PREDICTED ELEVATOR MANEUVER CONTROL VERSUS TRIM	52
4.4-7	PREDICTED TRIM RUNAWAY OVERRIDE FORCES	53
4.4-8	PREDICTED HYDRAULIC DISCONNECT 'G' TRANSIENT	54



4.4-9	PREDICTED HYDRAULIC DISCONNECT FORCE TRANSIENT	55
4.4-10	PREDICTED MANUAL REVERSION FORCES	56
5.0-1	EMPENNAGE GROUND TEST SET-UP	63
5.2-1	ELEVATOR - COLUMN GEARING	64
5.2-2	PREDICTED ELEVATOR AUTHORITY	65
5.2-3	GEARED TAB VS ELEVATOR DEFLECTION	66
5.2-4	FEEL CHARACTERISTICS - 0 KNOTS	67
5.2-5	FEEL CHARACTERISTICS - 60 KNOTS	68
5.2-6	FEEL CHARACTERISTICS - 90 KNOTS	69
5.2-7	FEEL CHARACTERISTICS - 120 KNOTS	70
5.2-8	FEEL CHARACTERISTICS - 160 KNOTS	71
5.2-9	BREAKOUT FORCES VERSUS AIRSPEED	72
5.2-10	FEEL GRADIENT	73
5.2-11	FEEL PRESSURE - 'A' COMPUTER	74
5.2-12	FEEL PRESSURE - 'B' COMPUTER	75
5.2-13	FEEL COMPUTER RESPONSE	76
5.2-14	SAS SERVO AUTHORITY	77
5.2-15	ELEVATOR PCU FREQUENCY RESPONSE - DUAL HYD	78
5.2-16	ELEVATOR PCU FREQUENCY RESPONSE - SINGLE HYD	79
6.1-1	FLUTTER INSTRUMENTATION	91
6.1-2	EMPENNAGE RESPONSE TO RUDDER KICK	92
6.1-3	EMPENNAGE RESPONSE TO ELEVATOR KICK	93
6.2-1	GROSS WEIGHT - C.G. SCHEDULE	94
6.2-2	ELEVATOR TO TRIM	95
6.2-3	TAKEOFF ROTATION	96
6.2-4	PITCH ATTITUDE CHANGE - 120 KNOTS	97
6.2-5	PITCH ATTITUDE CHANGE - 60 KNOTS	98
6.2-6	STOL LANDING	99
6.2-7	ELEVATOR MANEUVER REQUIREMENTS	100
6.2-8	ELEVATOR PER 'G'	101
6.2-9	ELEVATOR HINGE MOMENT COEFFICIENT	102
6.2-10	ELEVATOR BLOWDOWN	103
6.2-11	HORIZONTAL TAIL LOADS	104
6.2-12	ELEVATOR - COLUMN GEARING	105



6.2-13	GEARED TAB VERSUS ELEVATOR	106
6.2-14	FEEL CHARACTERISTICS	107
6.2-15	FEEL CHARACTERISTICS	108
6.2-16	FEEL CHARACTERISTICS	109
6.2-17	CALCULATED FEEL FORCES	110
6.2-18	FEEL PRESSURES - 'A' COMPUTER	111
6.2-19	FEEL PRESSURES - 'B' COMPUTER	112
6.2-20	CONTROL SYSTEM DYNAMICS	113
6.2-21	HYDRAULIC DISCONNECT FORCE TRANSIENTS	114
6.2-22	MANUAL REVERSION FORCES	115
6.2-23	STEADY SIDESLIP	116



NOMENCLATURE

AWJSRA	--	Augmentor Wing Jet STOL Research Aircraft
C_{He}	--	Elevator hinge moment coefficient
$C_{He\delta_t}$	--	$\partial C_{He} / \partial \delta_t$, elevator hinge moment coefficient variation with geared tab deflection
F_p, F_s	--	Column force
G/S	--	Glide slope
h	--	Altitude
L_T	--	Horizontal tail lift
M_T	--	Horizontal tail bending moment @ 25% MAC
N_H	--	High pressure engine shaft speed
n_z	--	normal load factor
PCU	--	Power control unit
PLF	--	Power for level flight
PIO	--	Pilot induced oscillation
qc	--	impact pressure
SAS	--	Stability augmentation system
V_A	--	Design maneuvering speed
V_B	--	Design speed for maximum gust intensity
V_c	--	Design cruise speed
V_D	--	Design dive speed
V_e	--	Equivalent airspeed
V_f	--	Design flap speed
β	--	Sideslip angle
γ	--	Flight path angle



δ_C -- Column position
 δ_e -- Elevator position
 δ_F -- Flap position
 $\delta_{N,V}$ -- Pegasus nozzle position
 δ_R -- Rudder position
 δ_t -- Geared balance tab position
 δ_{TT} -- Trim tab position



2.0 INTRODUCTION


In October 1972, The Boeing Company was awarded Contract NAS2-7293 to design a powered elevator control system for the Augmentor Wing Jet STOL Research Airplane (AWJSRA). The contract included component fabrication, refurbishment and modification of a government-furnished tail assembly.

The contract was subsequently enlarged to cover installation of the modified tail assembly and related components on the AWJSRA, as well as ground and flight testing to verify airworthiness of the powered elevator installation.

This document summarizes the modification program for the powered elevator system. The schedule and significant milestones of the program are summarized in figure 1.



ENGR			REVISED	DATE	PROGRAM SCHEDULE POWERED ELEVATOR SYSTEM ENGINEERING	MOD C-8A FIG. 2.0-1 D6-411489 Page 13
CHECK						
APR						
APR						



CONTRACT AWARD

SYSTEM DESIGN

**EMPENNAGE
REFURBISHMENT, FAB.,
AND ASSEMBLY**

AIRCRAFT MODIFICATION

GROUND TEST

TAXI AND FLIGHT TEST

DR ~ DESIGN REVIEW

SR ~ SAFETY REVIEW

FT ~ FUNCTIONAL TEST

FRR ~ FLIGHT READINESS REVIEW

3.0 AIRPLANE DESCRIPTION

3.1 GENERAL FEATURES

The AWJSRA is a 45,000 pound, 50 psf wing loading, turbo-fan powered airplane designed for research in the STOL terminal flight regime. The airplane is derived from a deHavilland C-8A "Buffalo" airframe. Augmentor-wing jet flaps, blown and drooped ailerons and leading edge slats have been added to produce high lift capability for STOL research. Wing span has been shortened to increase wing loading. Two Rolls Royce Spey 801SR jet engines provide blowing air to the flaps and ailerons via ducts as well as direct hot thrust through vectorable Pegasus nozzles. A three view of the airplane is shown in figure 3.1-1. Airplane operational data are presented in table 3-1.

The AWJSRA has two independent, equal capacity 3000 psi hydraulic systems using MIL-H-5606 fluid. The electrical system is powered by two engine driven 115/200 volt, three phase, 400 Hz brushless generators that are connected to normally isolated left and right a.c. busses and through rectifiers to the left and right d.c. busses. A 24 volt battery is connected to the left d.c. bus.

Lateral control is achieved through three control surfaces: ailerons, spoilers and outboard flap augmentor chokes, each contributing approximately a third of the roll control. The control surfaces are fully powered. Spoilers and chokes have single hydraulic sources, the ailerons are powered by dual hydraulics. A limited authority series SAS actuator is included in the lateral axis. Manual reversion control of the ailerons is possible following the loss of both hydraulic systems. The lateral control system is shown in figure 3.1-2.

Directional control is via a single double-hinged rudder. The surface is fully powered by a dual tandem actuator. A limited



authority series SAS actuator is included in the directional axis. No manual reversion is possible. Figure 3.1-3 shows the directional control system.

Longitudinal control is via a single elevator surface which provides both maneuver and trim control functions as the stabilizer incidence is fixed. Prior to the powered elevator modification, longitudinal control was entirely manual. A spring tab on the right side of the elevator was used to reduce stick forces. A tab on the left side manually operated by the pilot and automatically by a flap-trim interconnect, was used for trimming. The manual elevator control system is shown in figure 3.1-4.

3.2

ELEVATOR CONTROL PROBLEM

The AWJSRA was flown by Boeing and NASA-ARC 67 times with the manual spring tab elevator control system. Certain shortcomings of this system below 80 knots became almost immediately apparent.

Maximum elevator deflection was not possible without extremely high stick forces. Stick forces in excess of 100 pounds were required for full elevator deflection at 60 knots, as shown in figure 3.2-1. The elevator up float angle (figure 3.2-2) changed considerably below 80 knots due to mass and aerodynamic overbalance effects. This had an adverse effect on control feel and airplane response. The elevator dynamic response was poor. Figure 3.2-3 shows elevator position to lag pilot force by approximately 130 degrees at 0.5 Hz. This high control system phase lag made tight attitude control extremely difficult.

These shortcomings of the manual elevator control system had a detrimental effect on the evaluation of the AWJSRA in the STOL regime and led to the design of a fully powered elevator control system.



3.3

EXTENT OF MODIFICATION

Airplane modifications made to incorporate the powered elevator system were as follows:

1. A dual tandem moving body power control unit which directly powers the elevator surface was installed in the horizontal stabilizer.
2. The elevator spring tab was replaced by a geared balance tab with ratio $\sigma_t/\sigma_e = -0.7$.
3. The flap-trim tab interconnect was deleted.
4. A feel system was located in the vertical stabilizer to provide pilot feel forces.
5. An electric trim motor that moves the neutral point of the feel system was installed.
6. The hydraulic system was modified to provide the power to the elevator PCU, feel system and SAS actuator.
7. Structural modifications were made to the vertical and horizontal stabilizers as well as to the forward segment of the rudder surface.



TABLE 3-1
OPERATIONAL DATA.

I. PLACARDS

DESIGN FLAP SPEEDS

<u>F</u>	<u>V_F Knots</u>
75°	90
50°	90
30°	120
5.6°(UP)	160

FLAPS UP DESIGN SPEEDS

Gust V _B	= 140 knots
Maneuvering V _A	= 136
Design Cruise V _C = V _{MO}	= 160
Design Dive Speed	= 180

DESIGN LOADS

Flaps down $0 g \leq n_z \leq 2.0 g$
 Flaps up (5.6°) $-0.5 g \leq n_z \leq 2.25 g$

MAXIMUM ALTITUDE

15,000 feet

FLIGHT RULES

VFR

II. TYPICAL DESIGN FLIGHT CONDITIONS

TAKEOFF

$\delta_F = 30^\circ$, $\gamma = 6^\circ$, $v_e = 75$ kts, $\gamma = 15^\circ$ (2 engines, takeoff power, 45,000 lbs)

CRUISE

$\delta_F = \text{up}$, $\gamma = 6^\circ$, $v_e = 140$ to 160 kts, $\gamma = 0$

LANDING

$\delta_F = 65^\circ$, $\gamma = 70^\circ$, $v_e = 60$ kts, $\gamma = -7.5^\circ$, $\Delta n_{z \text{ margin}} = .35 g$

$\Delta v_{\text{margin}} = 16$ kts






FIG. 3.1-1


AD 1546 D

LATERAL CONTROL SYSTEM



NOTE: ELECTRIC TRIM AT RATE OF $\dot{\delta}_w = \pm 4.2$ DEG/SEC

REV SYM

**NOTE:**ELECTRIC TRIM AT RATE OF $\dot{\delta}_R = \pm .8 \frac{\text{DEG}}{\text{SEC}}$

MOD C-8A FIG 3.1-3


BOEING

No. D6-41489

PAGE 20

SPRING-TAB ELEVATOR CONTROL SYSTEM

FIG 3.1-4






FIGURE 3-2-1 -STICK FORCE AND TAB EFFECTIVENESS BASED ON
TAXI AND FLIGHT TESTING
SPRING TAB ELEVATOR CONTROL SYSTEM






FIGURE 3.2-2 -ELEVATOR FLOAT AT ZERO STICK FORCE DURING TAXI

SPRING TAB ELEVATOR CONTROL SYSTEM



REV SYM




FIGURE 32-3 -ELEVATOR DYNAMICS AT 60 KT TAXI
SPRING TAB ELEVATOR CONTROL SYSTEM

BOEING

No 106-111489

PAGE 21



4.0 POWERED ELEVATOR SYSTEM DESIGN AND ANALYSIS

4.1 DESIGN REQUIREMENTS

The powered elevator system has been designed to comply with the intent of the Federal Aviation Regulations, Part 25, except for deviations with respect to mechanical failure conditions. These deviations were considered acceptable for a research airplane. This allowed use of the existing single load path cable system and the single control surface and thereby minimized the cost of the modification.

Specific design requirements which determined the system configuration are as follows:

1. The powered elevator system shall provide stick forces compatible with one hand operation.
2. Loss of one hydraulic system shall not cause unsafe stick force per 'g' characteristics.
3. Elevator manual reversion shall be available for safe flight to a landing.
4. The control system shall be capable of accepting series SAS commands.
5. The control system shall be safely operable over the total flight envelope of the AWJSRA.

4.2 DATA BASE

The data base for the design of a powered elevator control system came from actual flight test results of the airplane, from the original DHC Buffalo, and from a piloted simulator study done at NASA-Ames in May 1971 (reference 1).

A fundamental assumption was that the existing elevator control surface had sufficient control power to meet maneuver and trim



requirements throughout the flight envelope. This was in fact verified by flight test and therefore allowed use of the existing control surface.

Elevator hinge moment data was generated by combining the tab elevator effectiveness ratio (figure 4.2-1) obtained from Boeing flight test results with the tab hinge moment coefficient $C_{H_{\delta t}}$ of the basic Buffalo. A linear coefficient was assumed for tab deflections below 10 degrees. Elevator hinge moment data for deflections greater than 15 degrees were estimated from stick force data of the spring tab control system with the tab stops contracted. Figure 4.2-2 shows the estimated elevator hinge moment coefficient with zero tab deflection as well as the coefficient for the proposed surface configuration.

The elevator per 'g' characteristic used in the calculations is shown in figure 4.2-3. This characteristic is basically unchanged from the existing configuration and therefore requires the same airplane gross weight - c.g. schedule to be maintained as with the manual elevator control system.

The piloted simulator study was used to evaluate handling quality improvements with a powered elevator as well as to determine basic system parameters such as elevator/column gearing, minimum elevator surface rates, SAS authority, trim rates. Major simulator results were as follows:

1. A 30 degree per second elevator rate is a minimum acceptable lower level.
2. At the approach condition a linear gradient with 30 pounds stick force at maximum column deflection results in good control feel. (This was later revised to 40 pounds at maximum deflection).



3. A flap trim interconnect is not necessary. (This was also confirmed by pilot opinion in a flight test of the airplane prior to the powered elevator modification).
4. An elevator trim rate of 2 degrees elevator per second represents an acceptable compromise between high speed and low speed trim rate requirements.
5. A control system gearing of -3.28 degrees elevator per inch of column deflection is satisfactory, although -4 was preferred. A gearing above -5 tended to cause PIOs, especially with flaps up.
6. A SAS authority of +5 degrees elevator represents a satisfactory lower limit in the STOL flight regime.

4.3

POWERED ELEVATOR SYSTEM DESCRIPTION

Pitch control on the AWJSRA is by means of a single elevator control surface located on a fixed stabilizer. No load elevator position limits are +15 degrees, -25 degrees. The elevator surface (figure 4.3-1) includes a full time geared tab with a balance ratio $\delta_t / \delta_e = -0.7$, as well as a trim tab used during manual reversion.

The longitudinal control system schematic is shown in 4.3-2. Pilot and copilot signals are transmitted by a single cable run from dual control columns (figure 4.3-3) to the aft elevator control quadrant in the vertical stabilizer. The control columns and cable run are essentially unchanged from the basic C-8A with the exception of two bias springs connected to the control column torque tube to counter the column mass unbalance in the vertical direction. From the aft quadrant, the pilot signals are transmitted to a dual tandem, moving body power control unit directly connected to the elevator surface. With one or two hydraulic systems operable, the PCU is irreversible and positions the elevator in response to pilot commands. The control system becomes reversible following the loss of both hydraulic systems. Elevator control for this condition is through a slop link in parallel with the PCU.



The control linkage between the aft quadrant and the elevator PCU is non-redundant. It includes a limited authority, series SAS actuator originally designed by Moog for the F-4 and subsequently modified for the AWJSRA application. The actuator includes a mechanical locking device that centers and locks the actuator when hydraulic power is lost or shut off. The control linkage and actuator installations are shown in detail in figures 4.3-4 and 4.3-5. A picture of the actual installation is shown in figure 4.3-6.

The elevator power control unit is a modified Grumman Gulfstream II elevator/aileron actuator. The actuator was one of several existing actuators investigated during the preliminary design phase. New actuators were not considered due to cost and schedule limitations. The actuator is a dual tandem, moving-body type, as shown in figure 4.3-7. Actuator modifications consisted of a new flow control valve and a strengthened head end output rod.

The installation has several noteworthy features. The actuator is specifically installed in a horizontal position to sense only motion in the fore-aft direction. The actuator input is thereby effectively decoupled from vertical deflections of the elevator hinge line. These represent a spurious input and can cause instability, particularly where high structural feedback is used.

The actuator and its input linkage (links 1 and 2) are mounted in and hence referenced to the horizontal stabilizer, while pilot signals transmitted by bellcrank 4 are referenced to the rear spar of the vertical stabilizer. Relative motion between the horizontal and vertical stabilizers could therefore induce inputs to the actuator. The horizontal pushrod (link 3) was therefore included to decouple the actuator from relative motion in the vertical plane. Structural feedback for actuator stability is obtained by mounting the input lever 2 on the vertical swing link 5. Deflections of the actuator support structure are thereby fed back to the valve in a stabilizing sense.



Pilot feel during powered operation is provided by a variable gradient feel system. The feel system comprises a feel computer, figure 4.3-8 and a feel control unit, figure 4.3-9. Both units are modified 727 components. The feel computer generates hydraulic pressure proportional to impact pressure as sensed by a pitot probe in the leading edge of the vertical stabilizer. The control unit utilizes the hydraulic feel pressure in conjunction with a fixed mechanical spring gradient to produce the artificial feel force. The hydraulic feel force generation is completely dualized. A differential pressure switch in the feel computer monitors the two feel pressure computations and generates a warning signal if a significant difference exists.

The feel system is connected to the aft elevator control quadrant via a preloaded spring push-pull rod (pogo). This pogo allows feel system overtravel during an out-of-trim condition, as well as permitting elevator control with a jammed feel system.

During manual reversion, pilot stick force is the sum of the aerodynamic forces, actuator and control system friction and damping forces, and the feel system mechanical gradient.

Pilot trim during powered operation is accomplished by shifting the neutral point of the feel system, and hence the control system. Trim authority is +9, -14 degrees elevator with a trim rate of 2 degrees/second. Trim authority is fixed for all flight conditions. Trim control is electrical only. Powered trim indication is via the elevator surface position indicator.

Trim control during manual reversion is via a tab on the elevator surface. The trim tab control system is shown in figure 4.3-10. Pilot control of the trim tab is mechanical only. A locking and indexing feature on the trim wheel prevents inadvertent mistrim during powered operation. Positive action is required by the pilot to unlock the trim wheel and allow its use for manual reversion trim.



Hydraulic power for the elevator control system is supplied by hydraulic systems 'A' and 'B'. The elevator PCU and feel system are supplied by both 'A' and 'B' systems; the SAS servo by system 'A' only. Supply pressure to the elevator PCU is reduced to 2440 psi. A relief valve and a low pressure warning switch provide protection against overpressure and underpressure. The hydraulic system schematic is shown in figure 4.3-11.

4.4

PREDICTED LONGITUDINAL CONTROL CHARACTERISTICS

Elevator trim requirements for 1 'g' flight are shown in figure 4.4-1. No trim change due to the powered elevator modification was predicted. Available elevator deflection during powered operation is shown on figure 4.4-2. Elevator deflection is limited at higher airspeeds by actuator blowdown. With both hydraulic systems operating, blow down from -25 degrees elevator starts at 100 knots and from +15 degrees at 118 knots. The 100 knot blow down speed allows maximum elevator deflection at the STOL approach speed with on hydraulic system lost as well as for dual hydraulics with loss of the geared tab.

Feel force characteristics, excluding friction, are shown in figure 4.4-3. The feel system provides a nearly constant 42 lbs/'g' for all flight conditions. The feel gradient is reduced by the pogo between the elevator aft quadrant and the feel control unit for force levels greater than 37 pounds column force.

The elevator power control unit has a no-load time constant of .04 second and a maximum no-load rate of 55 degrees/second. Both of these parameters are load sensitive and hence will vary with elevator position and airspeed, as shown on figure 4.4-4 and figure 4.4-5. Load effects at all trim conditions are small enough to ensure satisfactory PCU performance.

The control system is designed for a maximum SAS authority of + 8 degree elevator deflection. This SAS authority is a varying



percentage of pilot authority. The worst case occurs with trim at the maximum aircraft nose down trim limit (+9 degrees elevator), where +8 degrees SAS authority is equivalent to 104 percent pilot authority in the aircraft nose down direction (figure 4.4-6). A SAS hardover at this condition in the aircraft nose up direction will require SAS disconnect rather than override.

The power control unit input lever travel capability is limited to ± 2 degrees elevator deflection to minimize the amount of lost motion in the control system during the manual reversion mode. This, however, produces an undesirable effect during SAS operation, where the SAS actuator can backdrive the column $\pm 3.5^\circ$ if the pilot and the SAS both command maximum elevator in the same direction. This can be avoided during normal operation by automatically reducing the SAS command to zero as the pilot input approaches the maximum.

Trim control is electrical only, with no redundancy or mechanical backup. Trim runaways are a possibility, therefore, and must be countered by a corresponding pilot force. The force required to maintain airplane trim due to a maximum trim runaway at any one flight condition is shown on figure 4.4-7. Also shown is the force required for maximum elevator deflection with the most adverse trim runaway.

Manual reversion is automatically provided following the loss of both hydraulic systems. Airplane controllability during manual reversion covers three stages:

1. Hydraulic power on/off transient
2. Trim control
3. Maneuver control

Following the loss of two hydraulic systems, the elevator surface will automatically float to -4 degrees. If the airplane is not at a flight condition that requires -4 degrees trim, then a maneuver will result. The magnitude of the maneuver is dependent on the



difference between elevator float point and elevator trim prior to hydraulic power loss. The load factor transient for various conditions is shown on figure 4.4-8 while pilot force required to prevent this transient is shown on figure 4.4-9. Because of the magnitude of the possible transients, it is important that the pilot divert to 90 knots, flaps 30, as soon as possible if complete loss of hydraulic power can occur with one additional failure.

Trim for hands-off flight during manual reversion is possible through the existing trim tab. Trim control is only mechanical through the trim wheel. Authority is limited to ± 10.5 degrees elevator.

Maneuver control forces are considerably higher than in the powered mode. Aerodynamic loads are shown on figure 4.4-10. Control system friction, damping and the feel system centering spring will further increase the manual reversion loads.

The powered elevator system was analyzed to assure a flutter free design. In addition to the normal operating condition, certain failure cases were also investigated. These were

1. One and two hydraulic system failures
2. Geared balance tab rod failure

The analysis showed the elevator system to be flutter-free for all conditions investigated.



ELEVATOR VS SUB OF
SINUS TID AND TR: TID

$\delta_{12} + \delta_{12}$
DEC

DEC

DATA DERIVED FROM FLIGHT TESTS
WITH MANUAL ELEVATOR CONTROL SYSTEM

REF: F.1. 2-1, 5-2, 9-2, 9-3, 9-5, 12-1

FIGURE 4.2-1

REV SYM

PREDICTED ELEVATOR HINGE MOMENT COEFFICIENT




FIGURE 4.2-2

BOEING

NO D6-41489

PAGE 34

ELEVATOR PER G

NOTE:

- VALID FOR ALL WEIGHTS ALONG NOMINAL C.G. FUEL LOADING SCHEDULE
- STEADY FULL UP AT CONSTANT SPEED




FIGURE 4.2-3

POWERED ELEVATOR SURFACE CONFIGURATION




FIGURE 4.3-1






FIGURE 4.3-2.

CONTROL COLUMN INSTALLATION








FIGURE 4.3-3











FIGURE 4.3-5
REV A


Part No.	Part Name	Part Description	Part Quantity	Part Unit	Part Material	Part Finish	Part Notes
GC 85524	Link 1	Link 1	1	1	Steel	Black	
GC 85527	Link 2	Link 2	1	1	Steel	Black	
GC 85528	Link 3	Link 3	1	1	Steel	Black	
GC 85529	Link 4	Link 4	1	1	Steel	Black	
GC 85530	Link 5	Link 5	1	1	Steel	Black	
GC 85531	Link 6	Link 6	1	1	Steel	Black	
GC 85532	Link 7	Link 7	1	1	Steel	Black	
GC 85533	Link 8	Link 8	1	1	Steel	Black	
GC 85534	Link 9	Link 9	1	1	Steel	Black	
GC 85535	Link 10	Link 10	1	1	Steel	Black	
GC 85536	Link 11	Link 11	1	1	Steel	Black	
GC 85537	Link 12	Link 12	1	1	Steel	Black	
GC 85538	Link 13	Link 13	1	1	Steel	Black	
GC 85539	Link 14	Link 14	1	1	Steel	Black	
GC 85540	Link 15	Link 15	1	1	Steel	Black	
GC 85541	Link 16	Link 16	1	1	Steel	Black	
GC 85542	Link 17	Link 17	1	1	Steel	Black	
GC 85543	Link 18	Link 18	1	1	Steel	Black	
GC 85544	Link 19	Link 19	1	1	Steel	Black	
GC 85545	Link 20	Link 20	1	1	Steel	Black	
GC 85546	Link 21	Link 21	1	1	Steel	Black	
GC 85547	Link 22	Link 22	1	1	Steel	Black	
GC 85548	Link 23	Link 23	1	1	Steel	Black	
GC 85549	Link 24	Link 24	1	1	Steel	Black	
GC 85550	Link 25	Link 25	1	1	Steel	Black	
GC 85551	Link 26	Link 26	1	1	Steel	Black	
GC 85552	Link 27	Link 27	1	1	Steel	Black	
GC 85553	Link 28	Link 28	1	1	Steel	Black	
GC 85554	Link 29	Link 29	1	1	Steel	Black	
GC 85555	Link 30	Link 30	1	1	Steel	Black	
GC 85556	Link 31	Link 31	1	1	Steel	Black	
GC 85557	Link 32	Link 32	1	1	Steel	Black	
GC 85558	Link 33	Link 33	1	1	Steel	Black	
GC 85559	Link 34	Link 34	1	1	Steel	Black	
GC 85560	Link 35	Link 35	1	1	Steel	Black	
GC 85561	Link 36	Link 36	1	1	Steel	Black	
GC 85562	Link 37	Link 37	1	1	Steel	Black	
GC 85563	Link 38	Link 38	1	1	Steel	Black	
GC 85564	Link 39	Link 39	1	1	Steel	Black	
GC 85565	Link 40	Link 40	1	1	Steel	Black	
GC 85566	Link 41	Link 41	1	1	Steel	Black	
GC 85567	Link 42	Link 42	1	1	Steel	Black	
GC 85568	Link 43	Link 43	1	1	Steel	Black	
GC 85569	Link 44	Link 44	1	1	Steel	Black	
GC 85570	Link 45	Link 45	1	1	Steel	Black	
GC 85571	Link 46	Link 46	1	1	Steel	Black	
GC 85572	Link 47	Link 47	1	1	Steel	Black	
GC 85573	Link 48	Link 48	1	1	Steel	Black	
GC 85574	Link 49	Link 49	1	1	Steel	Black	
GC 85575	Link 50	Link 50	1	1	Steel	Black	
GC 85576	Link 51	Link 51	1	1	Steel	Black	
GC 85577	Link 52	Link 52	1	1	Steel	Black	
GC 85578	Link 53	Link 53	1	1	Steel	Black	
GC 85579	Link 54	Link 54	1	1	Steel	Black	
GC 85580	Link 55	Link 55	1	1	Steel	Black	
GC 85581	Link 56	Link 56	1	1	Steel	Black	
GC 85582	Link 57	Link 57	1	1	Steel	Black	
GC 85583	Link 58	Link 58	1	1	Steel	Black	
GC 85584	Link 59	Link 59	1	1	Steel	Black	
GC 85585	Link 60	Link 60	1	1	Steel	Black	
GC 85586	Link 61	Link 61	1	1	Steel	Black	
GC 85587	Link 62	Link 62	1	1	Steel	Black	
GC 85588	Link 63	Link 63	1	1	Steel	Black	
GC 85589	Link 64	Link 64	1	1	Steel	Black	
GC 85590	Link 65	Link 65	1	1	Steel	Black	
GC 85591	Link 66	Link 66	1	1	Steel	Black	
GC 85592	Link 67	Link 67	1	1	Steel	Black	
GC 85593	Link 68	Link 68	1	1	Steel	Black	
GC 85594	Link 69	Link 69	1	1	Steel	Black	
GC 85595	Link 70	Link 70	1	1	Steel	Black	
GC 85596	Link 71	Link 71	1	1	Steel	Black	
GC 85597	Link 72	Link 72	1	1	Steel	Black	
GC 85598	Link 73	Link 73	1	1	Steel	Black	
GC 85599	Link 74	Link 74	1	1	Steel	Black	
GC 85600	Link 75	Link 75	1	1	Steel	Black	



ELEVATOR
CONT


FIGURE 4, 3-6
D6-11489
Page 11

"Q" BELLOWS PRELOAD ADJUSTMENT



COMPUTER UNIT SCHEMATIC

CALC.	CHECK	APPD	APPD	REVISED	DATE	COMPUTER - FEEL SYSTEM	MOD C-9A
							FIG. 4.3-8
						THE BOEING COMPANY RENTON WASH	PAGE 43



FEEL CONTROL UNIT

FIG. 4.3-9



REV SYM

ELEVATOR TRIM TAB SYSTEM





FIGURE 4.3-10


REFERENCE

NO D6-41489

PAGE 45



1. Check for proper operation of all components.
 2. Check for proper operation of all components.
 3. Check for proper operation of all components.
 4. Check for proper operation of all components.
 5. Check for proper operation of all components.
 6. Check for proper operation of all components.
 7. Check for proper operation of all components.
 8. Check for proper operation of all components.
 9. Check for proper operation of all components.
 10. Check for proper operation of all components.




FOLDOUT FRAME

FOLDOUT FRAME

65-835342

1. Check for proper operation of all components.
 2. Check for proper operation of all components.
 3. Check for proper operation of all components.
 4. Check for proper operation of all components.
 5. Check for proper operation of all components.
 6. Check for proper operation of all components.
 7. Check for proper operation of all components.
 8. Check for proper operation of all components.
 9. Check for proper operation of all components.
 10. Check for proper operation of all components.



D6-41485
Page 116

1 PERRY, RICHARD WILLIAMSON &
2 301 1ST AVE NEW YORK 100 01, 100 02
3 100 03 & 100 04 BELLALANCA
4 NEW YORK 100 01
5 100 02 100 03 100 04 100 05
6 100 06 100 07 100 08 100 09
7 100 10 100 11 100 12 100 13
8 100 14 100 15 100 16 100 17
9 100 18 100 19 100 20 100 21
10 100 22 100 23 100 24 100 25
11 100 26 100 27 100 28 100 29
12 100 30 100 31 100 32 100 33
13 100 34 100 35 100 36 100 37
14 100 38 100 39 100 40 100 41
15 100 42 100 43 100 44 100 45
16 100 46 100 47 100 48 100 49
17 100 50 100 51 100 52 100 53
18 100 54 100 55 100 56 100 57
19 100 58 100 59 100 60 100 61
20 100 62 100 63 100 64 100 65
21 100 66 100 67 100 68 100 69
22 100 70 100 71 100 72 100 73
23 100 74 100 75 100 76 100 77
24 100 78 100 79 100 80 100 81
25 100 82 100 83 100 84 100 85
26 100 86 100 87 100 88 100 89
27 100 90 100 91 100 92 100 93
28 100 94 100 95 100 96 100 97
29 100 98 100 99 100 100 100 101
30 100 102 100 103 100 104 100 105
31 100 106 100 107 100 108 100 109
32 100 110 100 111 100 112 100 113
33 100 114 100 115 100 116 100 117
34 100 118 100 119 100 120 100 121
35 100 122 100 123 100 124 100 125
36 100 126 100 127 100 128 100 129
37 100 130 100 131 100 132 100 133
38 100 134 100 135 100 136 100 137
39 100 138 100 139 100 140 100 141
40 100 142 100 143 100 144 100 145
41 100 146 100 147 100 148 100 149
42 100 150 100 151 100 152 100 153
43 100 154 100 155 100 156 100 157
44 100 158 100 159 100 160 100 161
45 100 162 100 163 100 164 100 165
46 100 166 100 167 100 168 100 169
47 100 170 100 171 100 172 100 173
48 100 174 100 175 100 176 100 177
49 100 178 100 179 100 180 100 181
50 100 182 100 183 100 184 100 185
51 100 186 100 187 100 188 100 189
52 100 190 100 191 100 192 100 193
53 100 194 100 195 100 196 100 197
54 100 198 100 199 100 200 100 201
55 100 202 100 203 100 204 100 205
56 100 206 100 207 100 208 100 209
57 100 210 100 211 100 212 100 213
58 100 214 100 215 100 216 100 217
59 100 218 100 219 100 220 100 221
60 100 222 100 223 100 224 100 225
61 100 226 100 227 100 228 100 229
62 100 230 100 231 100 232 100 233
63 100 234 100 235 100 236 100 237
64 100 238 100 239 100 240 100 241
65 100 242 100 243 100 244 100 245
66 100 246 100 247 100 248 100 249
67 100 250 100 251 100 252 100 253
68 100 254 100 255 100 256 100 257
69 100 258 100 259 100 260 100 261
70 100 262 100 263 100 264 100 265
71 100 266 100 267 100 268 100 269
72 100 270 100 271 100 272 100 273
73 100 274 100 275 100 276 100 277
74 100 278 100 279 100 280 100 281
75 100 282 100 283 100 284 100 285
76 100 286 100 287 100 288 100 289
77 100 290 100 291 100 292 100 293
78 100 294 100 295 100 296 100 297
79 100 298 100 299 100 300 100 301
80 100 302 100 303 100 304 100 305
81 100 306 100 307 100 308 100 309
82 100 310 100 311 100 312 100 313
83 100 314 100 315 100 316 100 317
84 100 318 100 319 100 320 100 321
85 100 322 100 323 100 324 100 325
86 100 326 100 327 100 328 100 329
87 100 330 100 331 100 332 100 333
88 100 334 100 335 100 336 100 337
89 100 338 100 339 100 340 100 341
90 100 342 100 343 100 344 100 345
91 100 346 100 347 100 348 100 349
92 100 350 100 351 100 352 100 353
93 100 354 100 355 100 356 100 357
94 100 358 100 359 100 360 100 361
95 100 362 100 363 100 364 100 365
96 100 366 100 367 100 368 100 369
97 100 370 100 371 100 372 100 373
98 100 374 100 375 100 376 100 377
99 100 378 100 379 100 380 100 381
100 100 382 100 383 100 384 100 385
101 100 386 100 387 100 388 100 389
102 100 390 100 391 100 392 100 393
103 100 394 100 395 100 396 100 397
104 100 398 100 399 100 400 100 401
105 100 402 100 403 100 404 100 405
106 100 406 100 407 100 408 100 409
107 100 410 100 411 100 412 100 413
108 100 414 100 415 100 416 100 417
109 100 418 100 419 100 420 100 421
110 100 422 100 423 100 424 100 425
111 100 426 100 427 100 428 100 429
112 100 430 100 431 100 432 100 433
113 100 434 100 435 100 436 100 437
114 100 438 100 439 100 440 100 441
115 100 442 100 443 100 444 100 445
116 100 446 100 447 100 448 100 449
117 100 450 100 451 100 452 100 453
118 100 454 100 455 100 456 10

[illegible][illegible]

65-03534	2	100-48	△
----------	---	--------	---

~~FOLDOUT FRAMES~~

65-835342

FOYD OUT FRAME




FIGURE 4.4-1






FIGURE 4.4-2



MODIFIED C-8A




FIGURE 4.4-3




FIGURE 4.4-4



PREDICTED
CONTROL SYSTEM PERFORMANCE
SINGLE HYDRAULICS







FIGURE 4.4-5



INCREMENTAL ELEVATOR
DEFLECTION $\Delta \delta_0 = \text{deg}$



CALC			REVISED	DATE	<p>PREDICTED ELEVATOR AUTHORITY VS TRIM</p> <p>THE BOEING COMPANY</p>	MOD C-8A
CHECK						FIG 4.4-6
APR						PAGE 52
APR						PC-1180



CALC			REVISED	DATE	PREDICTED TRIM RUNAWAY OVERRIDES FORCES	NOD C-BA
CHECK						FIG 4.4-7
APR						PAGE 53
APR						DI-1, 1459
THE BOEING COMPANY						

BOOST ON-OFF INCREMENTAL LOAD FACTOR TRANSIENT

0.71 $\frac{g's}{s}$

PREDICTED
DISCONNECT TRANSIENT
HYD. POWER OFF





FIGURE 4.4-B





CALC		REVISED	DATE	PREDICTED BOOST OFF STICK FORCES TO MAINTAIN 1 G FLIGHT	FIG 4.4-9
CHECK					
APR					
APR					
				THE BOEING COMPANY	PAGE 55 10-11489




FIGURE 4.4-10



5.0

ENGINEERING GROUND TESTS

Engineering ground tests on the powered elevator system were conducted in two phases. Initial tests were made on the modified empennage at Boeing, Seattle between May 30, 1973 and June 11, 1973. The horizontal and vertical stabilizers were mated and installed in their normal position for these tests, as shown in figure 5.0-1. The empennage was subsequently shipped to NASA-Ames Research Center for mating with the Mod C-8A airframe. Final ground tests were performed on the airplane between July 2, 1973 and July 16, 1973.

The purpose of the ground tests was to determine the operating characteristics of the powered elevator system and to verify that it was satisfactory for flight. All tests were conducted with the elevator surface unloaded. Tests conducted fall into two categories:

1. Control system proof and operations test
2. Control system performance tests

Test results are described below.

5.1

PROOF AND OPERATIONS TEST

The elevator control system was shown to withstand limit load with no permanent deformation or tendency to jam.

The control system was incrementally loaded through the control columns to a maximum combined pilot effort of 450 pounds in the push and 400 pounds in the pull direction. Hydraulic power to the elevator PCU was engaged for the test. The elevator surface was blocked at -25 degrees for the push test and +10 degrees for the pull test. The lower force in the pull direction was due to a testing error, rather than by intent. With the maximum load applied to the column, the control system was inspected and found free from potential jams. Following the test, the system was visually inspected and the rigging checked to verify that no permanent deformation had occurred.

5.2

CONTROL SYSTEM PERFORMANCE TESTS

5.2.1

Control System Gearing

Elevator versus Control Column - The elevator-to-column gearing in the airplane nose up direction was lower than predicted due to



a reduced aft quadrant-to-column deflection. The control column aft travel limit was therefore increased to 14 degrees to allow full trailing edge up elevator to be commanded.

The PCU installation was found to have a lower than predicted structural stiffness. This will cause a reduction in the elevator PCU steady state gain with increasing airspeed and hence a reduction in elevator-column gearing as shown in figure 5.2.1. For airspeeds below 110 knots, the maximum nose up elevator will be limited by the available aft column travel, as shown in figure 5.2-2. This reduction in elevator authority is not expected to cause a problem.

Elevator versus Geared Tab Deflection - The predicted and actual geared tab-to-elevator deflection is shown in figure 5.2-3. The actual gear ratio δ_t / δ_e is -0.6 for elevator deflections between +10 degrees and -14 degrees, compared to a predicted ratio of -0.7. In addition, the geared tab neutral rig point is at -4. degrees elevator instead of -3 degrees. These deviations were considered acceptable for flight test.

5.2.2 Control System Feel Characteristics

Feel characteristics were determined for varying airspeeds and trim conditions by moving the pilot's control column and recording column force versus elevator position on an x-y plotter.

Initial tests showed the control system to have 4.1 pounds friction, of which 3.1 pounds were due to the control column and control cables. Total system friction was subsequently reduced to 3.3 pounds by reducing the cable rig load from 118 pounds to 80 pounds and realigning three fairleads. All ground test results are for this configuration unless noted otherwise. Typical test data at various simulated airspeeds are shown in figures 5.2-4 through 5.2-8.



Breakout and friction forces as a function of trim and airspeed are shown in figure 5.2-9. The forces generally increase with increasing nose down trim and increasing airspeed, and are symmetric with respect to push and pull. The average breakout force is 6.0 pounds, the average friction force 3.9 pounds. Positive centering, but not absolute centering was found for all conditions. Some reduction in friction is expected in flight due to increased vibration. This will reduce the breakout forces and improve system centering.

The theoretical and actual feel gradient (F_s/δ_e) as a function of airspeed is shown in figure 5.2-10. Test results are valid for ± 5 degrees elevator deflection about zero degrees elevator trim. The ground test results deviate from theoretical in two respects:

- a. The feel gradient in the column aft direction is approximately 20% lower than in the column forward direction.
- b. The feel gradient error (theoretical gradient - actual gradient) becomes increasingly more negative with increasing airspeed for both column forward and aft.

The feel gradient variation between push and pull is attributed primarily to non-linear gearing. The feel gradient did not vary appreciably with either hydraulic system A, B, or A and B engaged.

5.2.3 Elevator Feel System Computer

The elevator feel computer static gain was checked by applying varying pitot pressures corresponding to the full airspeed range and recording the resultant feel pressures. Final ground test results agree fairly well with the theoretical results, although an inconsistency was noted in the 'A' channel results between the final test results and earlier tests. Figures 5.2-11 and 5.2-12 show theoretical and actual results for systems A and B.

Both feel computers A and B were found to be sensitive to feel pressure flow demands. Figure 5.2-13 shows a typical response. Feel pressure A and B variations are 146 psi and 85 psi respectively



about a 240 psi nominal feel pressure, with a maximum elevator rate of approximately 34 degrees per second.

The feel computer performance is dependent on the vibration environment of the computer. With no vibration, the feel computer has up to 100 psi feel pressure hysteresis. At 60 knots, this would result in a 30% variation in feel gradient. With a small amount of vibration, hysteresis is less than 30 psi, reducing the feel gradient variation to less than 10%. Improved performance will require an increase in the pressure control valve flow gain and reduced valve spool friction.

The feel computer pitot system contains two small drain holes. There was some indication that these drain holes resulted in a lower pitot pressure at the feel computer than at the pitot source. The ground test was therefore conducted with the drain holes plugged. The effect of these drain holes on feel pressure will be evaluated during flight test.

It was possible to trigger a sustained oscillation in the 'B' system feel computer by applying a simulated airspeed of 100 knots or greater and then switching the 'B' hydraulic system supply pressure off and then back on. The 'B' system would immediately oscillate at approximately 7 Hz and + 200 psi. This oscillation could be stopped by reducing airspeed. It was not possible to induce the oscillation by moving the control column. The oscillation could also not be induced in the 'A' system feel computer. Although the oscillation could be felt in the control column, it did not couple with the elevator PCU. The oscillation was further investigated during flight test to determine if the oscillation is aided by the pitot pressure ground test equipment.

5.2.4 Control System Resolution

The control column-elevator resolution was found to be good, with no apparent deadzones. Elevator position hysteresis for full column travel is 0.3 degree elevator,



5.2.6

Trim System

Trim authority for the powered elevator system was found to be +8.2 degrees, -14.8 degrees elevator. The no-load trim rate was 2.1 degrees elevator per second nose up and 2.3 degrees per second nose down. These rates were achieved after inserting a 3 ohm resistor in series with the motor armature circuit. Without the resistor the trim rate was 2.9 degrees per second nose up and 3.1 degrees per second nose down. The trim rate appeared to be insensitive to aiding loads, but decreases approximately 20 percent for opposing loads.

5.2.7

Elevator SAS Actuator

The SAS actuator has a maximum authority of ± 5 degrees elevator, corresponding to an actuator stroke of $\pm .32$ inch. This authority is independent of elevator position provided that the total elevator command does not exceed + 15 degrees or -25 degrees. The SAS authority may be increased to a maximum of -7.5 degrees, +7.9 degrees elevator (corresponding to $\pm .5$ inch SAS actuator stroke) by removing the internal actuator stops.

The elevator to SAS actuator static gain was found to be 16 degrees/inch. This gain is essentially independent of elevator trim. (Figure 5.2-14).

The SAS actuator has a maximum no-load rate of ± 33 degrees elevator per second. Actuator centering and locking following disengagement was positive under all conditions tested. Time to center from maximum stroke is approximately 1.5 seconds. System resolution for SAS actuator inputs was found to be excellent. The hysteresis between SAS command and elevator surface position due to control system non-linearities was found to be .07 degree elevator.



5.2.5 Control System Dynamic Response

The overall control system response to pilot inputs was evaluated by "sinusoidally" moving the control column and recording column force, column position and elevator position. Test results show the elevator to closely follow the control column inputs.


Typically, the elevator position lags the column force by approximately 30 degrees and column position by approximately 10 degrees at a frequency of 1.4 radians/second. The damping of the mechanical control system is satisfactory, with the column undergoing only one overshoot when displaced and allowed to center.

The dynamic response of the elevator power control unit (PCU) was determined by sinusoidally driving the PCU input through the SAS actuator. Test results showed the damping to be close to the predicted value, but the natural frequency to be 9.0 rad/sec lower. Figures 5.2-15 and -16 show the frequency response for both one and two hydraulic systems. Static load tests showed the low natural frequency to be due to a considerably lower than predicted structural stiffness. The reduction in natural frequency should have no effect on pilot or autopilot control of the airplane, since the gain and phase shift below 10 radians/second is relatively unchanged between the predicted and actual response.

The maximum no-load elevator rate was found to be 54 degrees per second trailing edge up and 61 degrees per second trailing edge down.


Ground test results showed the power control unit installation to be stable with either hydraulic system A, B, or A and B engaged. The installation is however dependent on structural feedback for stability, as the PCU could be made to oscillate by locking out this feedback in either one or both directions. The maximum structural feedback is limited by stops in order to control the magnitude of the load seen by the PCU reaction link. Because of the lower structural stiffness, these stops were adjusted to prevent bottoming under full aerodynamic load.





FAND 038947

ELEVATOR POSITION, $\delta_e \sim \text{DEG}$



AIRSPEED, $V_e \sim \text{KTS}$

CALC		REVISED	DATE
CHECK			
APR			
APR			
INK	HEMBREE	1-21-74	


PREDICTED
ELEVATOR AUTHORITY

THE BOEING COMPANY

MOD
C-8A
FIG 5-2-2
PAGE 65
D6-41489


GROUND TEST
TEST CONDITION 3.2.4-4



V_e : 0 KFS
TRIM: $0^\circ \delta_e$
HYD SYS: A & B



MASSACHUSETTS
AVES RESEARCH CENTER


FIGURE 5-2-4





GROUND TEST
TEST CONDITION 3.2.4-6

V_e : 90 KHz
TRIM : $0^\circ \delta_e$
HYD SYS: A & B
 P_{FB} : 372 PSI



GROUND TEST
TEST CONDITION 3.2.4-7

V_e : 120 KH

TRIM : $0^\circ \delta_e$

HYD SYS : A & B


FEEL PRESSURE : 750 psi


143.5
MILS INST. AROUND TRIM

FIGURE 5.2-7

DC-41489


Page 70






CALC			REVISED	DATE	CONTROL SYSTEM BREAK-OUT AND FRICTION FORCES	MOD C-8A
CHECK						FIG 5.2-9
APR						PAGE 72
APR						D6-41489
INK	HEMBREE	1-22-74			THE BOEING COMPANY	

FEEL GRADIENT
~ % THEORETICAL



FEEL FORCE GRADIENT
 $F_p / \delta_e \sim \text{LBS/DEG}$



NOTE: TEST RESULTS
VALID FOR 0°
ELEVATOR TRIM

GROUND TEST RESULTS

□ PUSH
△ PULL

AIRSPED, V_g ~ KTS

CALC		REVISED	DATE	FEEL FORCE GRADIENT VS AIRSPEED	MOD C-8A
CHECK					
APR					
APR					
INK	HEMBREE	1-22-74		THE BOEING COMPANY	
				PAGE 73	MOD
				D6-41489	FIG 5.2-10


FEEL COMPUTER

REGULATION TOLERANCES
 0-500 PSI $\pm 8\%$
 500-1000 PSI $\pm 6\%$
 1000-1500 PSI $\pm 5\%$

CRITICAL DESIGN PT.
 $P_f = 218 \pm 15$ PSI
 $q_c = 12.2$ PSF

CRITICAL DESIGN PT.
 $P_f = 908 \pm 54$ PSI
 $q_c = 57.1$ PSF

GROUND TEST DATA



FEEL COMPUTER PERFORMANCE

'A' SYSTEM

THE BOEING COMPANY

MOD

C-84

FIG. 52-11

PAGE 11
 DC-11189

REVISD DATE

CALC

CHECK

APR

APR

FEEL COMPUTER

REGULATION TOLERANCES

0-500 PSI $\pm 8\%$

500-1000 PSI $\pm 6\%$

1000-1500 PSI $\pm 5\%$

REGULATED PRESSURE ABOVE RETURN ~ PSI ~ PSF

1400
1300
1200
1100
1000
900
800
700
600
500
400
300
200
100

CRITICAL DESIGN P_T
 $P_T = 213 \pm 15$ PSI
 $q_c = 12.2$ PSF

CRITICAL DESIGN P_T
 $P_T = 908 \pm 54$ PSI
 $q_c = 571$ PSF

GROUND TEST DATA

223 MIN.
203 MIN.

0 10 20 30 40 50 60 70 80 90

$q_c \sim$ DYNAMIC AIR PRESSURE ~ PSF

FEEL COMPUTER PERFORMANCE

'G' SYSTEM

THE BOEING COMPANY

N/D
C-8A

FG-52-12

PAGE 75
DG-11189

REVISED DATE

CALC


CHECK

APR

APR

INX

JENSEN




GROUND TEST
FEEL COMPUTER DYNAMIC RESPONSE

FIGURE 5.2-13

D6-41489

Page 76




CALC		REVISED	DATE
CHECK			
APR			
APR			

ELEVATOR SAS SERVO POSITION AUTHORITY AND GAIN

THE BOEING COMPANY


MOD
C-BA
FIG 5.2-14
PAGE 77
10-2-41-80



CALC		REVISED		DATE		ELEVATOR FREQUENCY RESPONSE SINGLE HYDRAULICS THE BOEING COMPANY		MOD C-BA	
CHECK								FIG 5-2-15	
APR								PAGE 18	
APR								D6-41489	

CONTRACT NO.

GROUND TEST DATA



GROUND TEST DATA

MOD	ELEVATOR FREQUENCY RESPONSE			
C-8A	DUAL HYDRAULICS			
FIG 5.2-16	THE BOEING COMPANY			
PAGE 79				
D6-11489				
CONTRACT NO.				
CALC			REVISED	DATE
CHECK				
APR				
APR				

6.0

TAXI AND FLIGHT TESTS

The flight test program for the powered elevator modification on the Mod C-8A airplane was conducted by NASA-ARC with Boeing support at Moffett Field, California. Purpose of the tests was to demonstrate airworthiness and to determine the operating characteristics of the powered elevator system.

Flight testing consisted of one taxi test and five flight tests. Testing was conducted on the following dates:

<u>Flight</u>	<u>Date</u>	<u>Purpose</u>
Taxi	Aug 28, 1973	Taxi tests to 110 knots for flutter checks and control evaluation.
No. 68	Sept 19 "	Flight test to 120 knots
69	" 21 "	Flight test to 140 knots
70	" 21 "	Flight test to 160 knots
71	" 25 "	Flight test to 160 knots
72	" 26 "	Flight test to 180 knots

A three-week delay occurred between the taxi test and first flight (flight 68) due to an electrical system problem unrelated to the powered elevator installation. The flight test was planned for a minimum of four flights to allow flutter clearance in 20-knot speed increments. The test sequence generally followed on each flight was to initially conduct the flutter checks up to the maximum air-speed designated. Following this the control system evaluation was conducted for the remainder of the flight. Recorded flight test data were analyzed for critical parameters prior to permitting the next flight.

During the flight test program, the airplane was flown at airspeeds ranging between 49 knots (flaps 65 stall) and 180 knots IAS. Flight weights ranged from 46,000 pounds at takeoff to a minimum of 36,000 pounds at landing. The airplane center of gravity varied between 29% and 31% MAC. Variations in load factor from 0.1 g to 1.9 g were attained. The airplane was sideslipped to 12 degrees. Angle of attack varied between approximately -3 degrees and +26



degrees (flaps up stall). All tests were conducted below 10,000 foot altitude.

Pilot reports showed the powered elevator system to perform very satisfactorily throughout the flight envelope, with no adverse characteristics noted.

6.1

FLUTTER TESTS

The flight envelope was flutter cleared in 20 knot speed increments. On each flight, a range of speed points was tested in five knot increments. The airplane was excited by abrupt pilot inputs to the rudder and elevator, with pilot feel being relied on to detect excessive oscillations. Recorded data were analyzed after each flight to determine the damping levels and trends of the various modes of vibration versus airspeed. Clearance to higher speeds for the next flight was given when the results were found satisfactory.

The vertical tail, horizontal tail, rudder and elevator were instrumented to measure their response. A diagram showing the instrumentation is presented in figure 6.1-1. After the third flight, the accelerometers at the upper and lower portions of the vertical tail were relocated in the cockpit because of pilot comments about the vibration level. No problem was found.

The results of the flight flutter tests showed that the Modified C-8A airplane with powered elevator control system satisfied the flutter clearance speeds with adequate damping. The responses of the rudder, elevator and tabs are heavily damped for all the speed points. The two important empennage modes are antisymmetric modes at about 2.8 Hz (stabilizer vibrating in a roll sense), and 6.2 Hz (stabilizer vibrating in a yaw sense). Figures 6.1-2 and -3 show examples of the response to a rudder and an elevator kick respectively at 180 KIAS.



6.2

LONGITUDINAL CONTROL EVALUATION

The longitudinal control system was evaluated at the following flight conditions to verify satisfactory operation:

1. Takeoff and climb at 90 knots, flaps 30
2. Cruise at 120 knots, flaps up
3. Cruise at 160 knots, flaps up
4. Descent at 120 knots, flaps up
5. Holding at 90 knots, flaps 30
6. Approach at 90 knots, flaps 30
7. Approach at 60 knots, flaps 65

In addition to routine flight maneuvers, specific evaluation tasks consisted of sinusoidal column inputs, column step changes, rapid pitch attitude changes, sideslips, wind-up turns, pushover/pullups and stalls. The evaluation was conducted for both one and two hydraulic systems.

6.2.1

Elevator Control Power

Prior to first flight, the airplane was ballasted to obtain the same airplane gross weight/center of gravity schedule as previously flown with the spring tab elevator control system. This schedule is shown in figure 6.2-1.

The elevator required for steady 1 'g' trim points conducted during the flight test program is presented in figure 6.2-2. The trim points correspond to typical climb, level flight and descent conditions at flaps 5.6 flaps 30 and flaps 65. Major parameters are listed in table 1. As expected, elevator trim requirements were unchanged by the powered elevator modification.

Elevator maneuver requirements are well within the capabilities of the powered elevator control system. The maximum trailing edge up elevator occurred during the flare, where -19.1 degrees elevator trailing edge up was reached (flight 70, IRIG 23:55:47). Maximum trailing edge down elevator of +9.0 degrees was attained during ± 9.5 degrees per second pitch rate maneuvers at the STOL approach



REV SYM

TABLE 1

Flight No.	Time	Weight x 10 ³	Flaps	Percent N _H	δ_N	h	γ	V _e	δ_e
72	21:57:57	45.2	6	97.2	6	5210	+4.4	127	-4.3
70	23:21:00	41.5	6	92.4	6	5777	+2.4	96	-7.2
70	23:21:39	41.4	6	92.4	6	6058	+2.5	88	-8.9
69	16:15:20	42.9	6	92.7	6	4920	0.6	123	-5.4
	16:54:20	42.6	6	92.7	6	5079	-0.4	133	-4.9
	17:00:40	41.8	6	94.0	6	5156	0.4	144	-3.8
70	23:22:14	41.4	6	92.4	6	6329	0.9	75	-10.2
	23:22:55	41.3	6	92.4	6	6385	-0.3	69	-12.8
72	22:01:07	44.8	6	94.8	6	6990	-0.4	164	-2.9
	22:03:52	44.5	6	96.6	6	6412	0.8	172	-3.1
	22:06:30	44.0	6	96.6	6	6835	0.6	175	-2.8
	22:12:46	43.1	6	99.7	6	7408	0.2	191	-2.5
70	23:23:35	41.2	6	92.4	6	6345	-2.3	66	-17.0
72	22:16:46	42.6	6	86.9	6	5996	-8.2	179	-3.4
69	16:46:56	43.7	30	97.0	6	2978	5.1	95	-0.6
	16:48:20	43.2	30	97.2	6	4384	6.3	82	-1.2
	16:49:40	43.1	30	97.2	6	5171	3.4	106	-0.6
70	22:59:35	43.9	30	93.8	6	5870	1.6	97	-1.2
72	21:55:07	45.6	30	97.0	6	2615	2.2	107	-1.2
	21:55:43	45.5	30	97.0	6	3187	5.1	86	-2.4

BOEING

NO D6-41489

PAGE 83

REV SYM

Flight No.	Time	Weight x 10 ³	Flaps	Percent NH	σ_N	h	δ	V _e	σ_e
69	17:06:18	41.3	30	94.1	6	5423	+1.3	105	-1.5
	17:07:28	41.2	30	93.3	6	5590	0.6	97	-2.7
	17:09:11	41.1	30	92.6	6	5541	-0.1	84	-4.4
72	22:31:10	40.8	30	93.8	6	7118	-0.8	98	-2.7
69	17:10:28	40.8	30	90.2	6	5150	-3.3	84	-6.2
	17:12:34	40.6	30	90.2	6	4404	-3.8	95	-4.7
	17:13:54	40.4	30	91.9	6	3880	-1.6	107	-2.4
72	22:22:28	41.9	30	94.5	6	7043	-1.9	106	-2.2
	22:33:50	40.5	80	87.6	6	5342	-5.6	96	-5.9
72	22:38:20	40.0	65	99.9	6	6985	+1.5	63	3.1
69	17:47:39	36.6	65	93.5	89	4003	-10.3	72	1.8
72	22:37:30	40.0	65	97.0	6	6838	-1.3	63	1.8
	22:40:32	39.7	65	93.8	70	6446	-8.1	67	0.7
	22:40:57	39.6	65	93.7	70	5891	-7.2	81	3.4
	22:41:48	39.5	65	93.7	70	5110	-10.7	56	-0.8
	22:42:32	39.4	65	93.5	70	4213	-7.0	78	3.0

BOEING

NO. D6-111489

PAGE 84



condition (flight 69, IRIG 17:27:10). Typical elevator maneuver requirement time histories are shown in figures 6.2-3, -4, -5, and -6. A summary of maneuver requirements is shown in figure 6.2-7.

Elevator per 'g' data obtained from wind-up turns at constant airspeed is shown in figure 6.2-8. Test results show no change due to the powered elevator modification.

6.2.2

Elevator Authority

The elevator is position limited to -25 degrees and +15 degrees surface deflection at no-load. During the taxi tests, deflections of -24.5 degrees and +14 degrees were demonstrated at a speed of 62 knots (IRIG 21:26:16).

Elevator reversals with one hydraulic system off were conducted at 106 knots in order to verify the predicted elevator authority at high speed; blowdown was not reached, however. The elevator hinge moment coefficient was therefore derived from elevator actuator loads measured during flight test and used to calculate a blowdown curve. The predicted and calculated hinge moment coefficient is shown in figure 6.2-9. The curve shows a considerably lower coefficient than predicted for large trailing edge up deflections. This results in an elevator blowdown speed of 170 knots instead of 100 knots, as shown on figure 6.2-10. It should be noted that the blowdown speed is further increased by any pilot effort transmitted to the elevator surface after elevator PCU blowdown is reached.

The increased elevator deflection capability at high speed could produce excessive tail loads. Figure 6.2-11 shows the horizontal tail load design envelope. Loads due to an abrupt elevator input of -25 degrees are shown for various airspeeds up to 170 knots. The structural design of the empennage is adequate for abrupt elevator maneuvers up to the design maneuver speed V_A (136 knots for the Mod C-8A). This will satisfy the requirements of FAR 25. However, full trailing edge up elevator above this speed would result in tail loads in excess of design loads.



Because of the relatively low pilot effort required to attain full trailing edge up elevator above 136 knots two recommendations are made:

1. Pilots should be cautioned not to make large and rapid elevator control inputs above 120 knots. Control forces should be kept below 40 pounds pilot effort.
2. The effect of reducing the elevator PCU supply pressure from its present value of 2440 psi to 1500 psi should be investigated and, if found acceptable, implemented. This would limit elevator deflection due to actuator output to a safe value, as shown in figure 6.2-10. Maximum elevator no-load rate would however be reduced from 54 degrees per second to 42 degrees per second.

The reduced supply pressure will only limit elevator deflections to a safe value if no pilot effort is transmitted to the elevator surface. Since this is a possibility once actuator blowdown is reached, the cautionary note should be retained regardless of any reduction in hydraulic supply pressure.

6.2.3

Control System Gearing

The elevator-to-column deflection at different airspeeds is shown in figure 6.2-12. The gearing decreases with increasing airspeed due to increased cable stretch and a reduction in the steady-state gain of the elevator PCU. At 62 knots the elevator-to-column gain between 0 and -10 degrees elevator is 1.65 deg/deg. This gain is reduced to 1.35 deg/deg at 180 knots. A greater reduction had been anticipated as a result of the engineering ground test data (figure 5.2-2) but did not occur due to the lower elevator hinge moment.

The geared tab-to-elevator deflection is shown in figure 6.2-13. The gearing is reduced from a nominal $\delta_t/\delta_e = -0.6$ at 62 knots to $\delta_t/\delta_e = -0.45$ at 180 knots. The reduction in balance ratio is of little significance since elevator control power and manual reversion forces are satisfactory.

The series SAS actuator was not activated during the flight test program. SAS actuator gearing could therefore not be checked.

6.2.4

Control System Feel Characteristics

Feel and centering characteristics were considered satisfactory by the pilots. Specific comments were that at 90 knots and 120 knots,



breakout forces were not noticeable and system centering was good. Feel gradients were found compatible with one-handed operation. Figures 6.2-14 and -15 show typical column force-elevator characteristics. Breakout forces are approximately 7.5 pounds, compared to 5.5 pounds obtained during the engineering ground tests. This difference is primarily due to a misaligned cable fairlead near body station 510.

The feel gradient characteristic obtained in flight is lower than predicted but is similar to ground test results. The variation in feel gradient between push and pull noted during the ground tests was not evident in the flight test data at the higher speeds primarily because the elevator is trimmed in a more linear region and elevator deflection are necessarily limited in magnitude. Figure 6.2-16 summarizes the feel gradient characteristic. The figure also shows stick force per 'g' data obtained from wind-up turns to vary between 30 pounds/'g' and 40 pounds/'g'. Calculated feel force characteristics based on the feel gradient data of figure 6.2-16 are shown in figure 6.2-17.

Feel computer operation from a pilot viewpoint was found to be satisfactory in that no feel force anomalies were noted. During the engineering ground tests, two discrepancies were noted:

1. A sustained feel computer oscillation could be induced in the "B" computer by cycling the hydraulic supply pressure at simulated airspeeds above 100 knots.
2. The elevator feel pressure warning light would light momentarily when cycling the elevator.

Neither of these items was found to occur during the flight test program.

The feel computer static gain is shown in figures 6.2-18 and -19. Both computer gains are on the high side, with 17.7 psi/psf and 16.3 psi/psf for computer A and computer B respectively compared to a nominal gain of 15.2 psi/psf.

In the steady state computers A and B track each other adequately, with the 'A' system feel pressures nominally 40 psi higher than the 'B' system pressures.



No feel pressure variations with pegasus nozzle position, flaps, one or two hydraulic systems, angle of attack or sideslip were noted. Any variation is small enough to be masked by the normal computer repeatability. For computer 'A' this is approximately 70 psi, for computer 'B', 40 psi. The better performance of the 'B' system appears to be due to lower valve spool friction.

6.2.5 Control System Dynamics

Control system dynamics with one or two hydraulic systems were judged satisfactory by the pilots. Release from control column steps produced one column overshoot at low speeds (60-90 knots) and two overshoots at higher airspeeds. The overshoots were not considered objectionable as the airplane did not appear to respond to them. Also, normal pilot activity added sufficient damping to eliminate overshoots.

The control system response to a column release at 127 knots and a "sinusoidal" column input at 60 knots is shown in figure 6.2-20. The control column at 127 knots has a natural frequency of 18.2 rad/sec and a damping ratio of approximately 0.35. The "sinusoidal" response at 60 knots shows the elevator position to lag column force by 13 degrees at a frequency of 1.1 radians/second. The phase lag did not vary significantly with airspeed. Control system phase lag at the "short period" frequency (approximately 0.8 radians/second at 60 knots and 3.0 radians/second at 160 knots) is therefore small enough to not affect airplane controllability.

6.2.6 Elevator Rate

The elevator rate was found to be satisfactory throughout the flight envelope. Rate saturation appears to have occurred for only one condition. This was an elevator reversal at 100 knots with one hydraulic system shut off.

Maximum elevator rates commanded during large maneuvers were as follows:

<u>Condition</u>	<u>Elevator Rate (Deg/Sec)</u>
Takeoff rotation	27°/S
Ten degree pitch attitude changes at 60 kts	34°/S
Landing flare	38°/S



6.2.7 Elevator Powered Trim System

The powered trim system has sufficient authority to trim the airplane for hands-off flight over the total flight envelope. The single speed trim rate was considered an acceptable compromise between high speed and low speed trim requirements. Trim runaways at any airspeed are easily overridden by the pilot and represent no safety problem.

6.2.8 Hydraulic Power Off Transients

Disconnect transients due to loss of hydraulic power were determined by monitoring elevator PCU loads during climb, level flight and descent conditions at various airspeeds.

Taxi test results showed the elevator float angle to be more positive than predicted. Since this directly affected the potential disconnect transients, a new trim tab setting was determined. The initial trim tab setting for the taxi tests and flight 68 was +1 degree trailing edge down. This was subsequently changed to +4 degrees for flights 69 and 70 and to +3.5 degrees for flight 72. All data has been corrected for this trim tab setting.

Results show that pilot forces between 37 pounds pull and 30 pounds push are required to maintain 1 'g' flight at any "normal" flight condition (figure 6.2-21). For flaps 30 flight conditions between 80 knots and 100 knots IAS, disconnect transients can vary between 30 pounds push for climb conditions and 20 pounds pull for descent conditions. During the manual reversion evaluation at 90 knots, flaps 30, a 16 pound push force was required to maintain trim. The force transient was gradual (approximately two seconds) and was considered mild by the pilot. This disconnect transient was zero when the trim tab was changed from +3.35 degrees (+3.5 degrees measured on the ground) to +2.95 degrees.

The present trim tab rigging (+3.5 degrees) is considered satisfactory. Disconnect transients over the total flight envelope are relatively small and should result in no hazardous condition.




6.2.9 Manual Reversion



Manual reversion was evaluated for approximately five minutes at a nominal 90 knots, flaps 30 flight condition. Control was deemed adequate for continued safe flight to a landing. The most prominent characteristic is a +3.2 degree elevator deadzone (equivalent to +1.2 inches column travel). Stick forces are higher than for powered operation but not objectionably so. Calculated manual reversion forces, based on the hinge moment coefficient of figure 6.2-9 are shown in figure 6.2-22. For "small" elevator deflections, forces agree closely with predicted values as can be seen by comparison with figure 4.4-10. Control forces are lighter than predicted for large elevator deflections. Satisfactory operation of the trim tab was also demonstrated.

6.3 RUDDER CUT-OUT EFFECT

The effect of the 1.5 ft² rudder cut-out on rudder control power was investigated by doing sideslips at 65 knots F65 and 90 knots F30. No detrimental effect was noted when compared against flight test results made prior to the modification, as shown in figures 6.2-23.

✈




 ACCELEROMETER READING IN DIRECTION OF ARROW
 CONTROL SURFACE ROTATIONAL DISPLACEMENT

CALC	R.J.F.	10/73	REVISED	DATE	<u>BUFFALO, C-8A MODIFIED</u> <u>WITH POWERED ELEVATOR</u> <u>FLIGHT FLUTTER TEST</u> <u>INSTRUMENTATION</u> THE BOEING COMPANY	MOD C-8A.
CHECK						FIG 6.1-1
APPD						PAGE 01
APPD						D6-41489

BOTH HYDRAULIC SYSTEMS OPERATING


VELOCITY = 180 KNOTS INDICATED



CALC	R.J.F.	5/11/73	REVISED	DATE	<u>BUFFALO C-8A MODIFIED</u> <u>WITH POWERED ELEVATOR</u> <u>FLIGHT FLUTTER TEST</u> <u>RESULTS</u> THE BOEING COMPANY	Mod C-8A
CHECK						FIG 6.1-2
APPD						PAGE 92
APPD						D6-41489


BOTH HYDRAULIC SYSTEMS OPERATING

VELOCITY = 180 KNOTS INDICATED



CALC	R.J.F.	6/11/73	REVISED	DATE	<u>BUFFALO C-8A MODIFIED</u> <u>WITH POWERED ELEVATOR</u> <u>FLIGHT FLUTTER TEST</u> <u>RESULTS</u>	MOD C-BA
CHECK						FIG 6-1-3
APPD						PAGE 93
APPD						D6-11489
					THE BOEING COMPANY	


WEIGHT ~ 1000 LBS




ENGR		REVISED	DATE	GROSS WEIGHT vs CG. BOEING	MOD C-84 FIG. 6-2-1 D6-41189 Page 94
CHECK					
APR					
APR					

SYM	FLAPS DZ%	WEIGHT LBS	N ₁ %	Y
①	UP	46000	61	80
②	UP	37000	61	80
③	UP	46000	102	80
④	UP	37000	102	80
⑤	UP	RANGE	AR	80 3% 613
⑥	UP	RANGE	PLF	80
⑦	30	37000	61	95
⑧	30	46000	102	95
⑨	30	RANGE	AR	95 3% 613
⑩	30	RANGE	PLF	95
⑪	65	46000	61	60
⑫	65	37000	102	60
⑬	65	RANGE	92	58-93, 75% 613

NOTE:
AR ~ AS REQUIRED
PLF ~ POWER FOR LEVEL
FLIGHT



CALC		REVISED	DATE	ELEVATOR TO TRIM OVER FLIGHT ENVELOPE	MOD C-BA
CHECK					FIG 6-2-2
APR					PAGE 95
APR					D6-41489
THE BOEING COMPANY					












FIGURE 6.2-4

DR-47-90

PAGE 37







FIGURE 6.2-6

○ #70 23:03:23 WIND-UP TURN
 Δ #70 23:08:39 " "
 ◇ #72 22:16:00 " "

ELEVATOR PER 'G' ~ deg/g




CALC			REVISED	DATE
CHECK				
APR				
APR				


ELEVATOR PER 'G'

THE BOEING COMPANY

N10D
 C-8A
 FIG 62-B
 PAGE 101
 1-115G

CALC			REVISED	DATE	MOD C-BA HG 6.2-9
CHECK					
APR					
APR					
ELEVATOR HINGE MOMENT COEFFICIENT					PAGE 102 IN 4.12429
THE BOEING COMPANY					





CALC		REVISED	DATE
CHECK			
APR			
APR			

ELEVATOR BLOWDOWN

THE BOEING COMPANY

Mod
C-8A
FIG 6-2-10
PAGE 103
11-1-1959

TAIL LIFT $L_T \times 10^{-3} = 165$

— DHC-5 DESIGN LOADS

--- MOD C-BA LOADS

TAIL MOMENT
 $M_T \times 10^{-6} = 11.16$

- UNCHECKED PITCH
- △ CHECKED PITCH
- GUST
- ◇ BALANCED MANEUVER
- ABRUPT ELEVATOR
- CHECK MANEUVER
- ⊕ ABRUPT ELEVATOR - POWERED


-25° δ_e AT 100 KTS
-25° δ_e AT 136 KTS
-25° δ_e AT 170 KTS

CALC			REVISED	DATE
CHECK				
APR				
APR				

HORIZONTAL TAIL LOADS

THE BOEING COMPANY

MOD
C-BA
FIG. 6-2-11
PAGE 104
DC-1, 10, 9



FLIGHT TEST CONDITIONS

- ① GROUND CHECK #72 21:42:42
- ② TAKE RUN 21:26:16 62 Kts
- ③ FLIGHT #70 23:11:30 127 Kts
- ④ FLIGHT #72 22:14:55 180 Kts

NOTE: CURVE ④ OFFSET BY -1.0° FOR CLARITY


CALC			REVISED	DATE
CHECK				
APR				
APR				

ELEVATOR - COLUMN GEARING

THE BOEING COMPANY

MOD
C-8A
FIG. 6-2-12
PAGE 105

- ① TAXI RUN 21:26:16 62 Kts
 ② FLIGHT #70 23:11:30 127 Kts
 ③ FLIGHT #72 22:14:55 180 Kts



ELEVATOR BALANCE TAB

GEARING-FLIGHT TEST DATA

THE BOEING COMPANY

C 3A

FIG 6.2.13

PAGE 106
 10-1-1950

CALC


CHECK

APR

APR


RECEIVED

DATE



ELEVATOR $S_a \sim \text{deg}$

CONTROLS CHECK
#72 IRIG 21:42:44



ELEVATOR $S_a \sim \text{deg}$


69 IRIG 17:21:16
62 KTS

FLIGHT TEST DATA


CALC		REVISED	DATE
CHECK			
APR			
APR			

CONTROL SYSTEM
FEEL CHARACTERISTIC
THE BOEING COMPANY

MOD
C-8A
FIG 6-2-14
PAGE 107
10-1-55



* 72 IRIG 23:11:30
 V_c 127 KTS



* 72 IRIG 22:14:55
 V_c 172 \rightarrow 195 KTS

FLIGHT TEST DATA

CALC			REVISED	DATE
CHECK				
APR				
APR				


CONTROL SYSTEM FEEL CHARACTERISTIC

THE BOEING COMPANY

1100
 C-8A
 FIG. 62-15
 PAGE 103
 21-2480


FEEL FORCE GRADIENT

FEEL FORCE GRADIENT $\frac{F_g}{V_0} = 10\text{g/deg}$



STICK FORCE PER 'G'

STICK FORCE PER 'G' $\frac{F_g}{V_0} = 10\text{g/deg}$




CALC		REVISED	DATE
CHECK			
APR			
APR			

FEEL CHARACTERISTICS

THE BOEING COMPANY

W10D
C-B A
FIG 62-76
PAGE 109
D6-11130

COLUMN FORCE F_p - lbs



NOTE: COLUMN FORCE F_p DOES NOT INCLUDE CONTROL SYSTEM FRICTION.
 CURVE BASED ON FLIGHT TEST RESULTS

CALC		REVISED	DATE
CHECK			
APR			
APR			

CALCULATED
ELEVATOR FEEL FORCE

THE BOEING COMPANY

MOD
 1-84
 FIG 6-2-17
 PAGE 110
 11-41430

FEEL COMPUTER A

REGULATION TOLERANCES

0-500 PSI $\pm 8\%$

500-1000 PSI $\pm 6\%$

1000-1500 PSI $\pm 5\%$

REGULATED PRESSURE ABOVE RETURN (PSI) ~ PSF

1400
1300
1200
1100
1000
900
800
700
600
500
400
300
200
100

CRITICAL DESIGN P_T
 $P_T = 213 \pm 16$ PSI
 $q_c = 12.2$ PSF

CRITICAL DESIGN P_T
 $P_T = 908 \pm 54$ PSI
 $q_c = 57.1$ PSF

FLIGHT 27 \diamond
FLIGHT 70 ∇
FLIGHT 72 \odot

FLIGHT TEST DATA

223 MAX

203 MIN

MOD
C-6A
Pg. 62-18
PAGE 111
D6-411489

THE BOEING COMPANY

$q_c \sim$ DYNAMIC AIR PRESSURE ~ PSF

INK
J. JENSEN
APR
APR
CHECK
CALC
REVISED
DATE

FEEL COMPUTER B

REGULATION TOLERANCES
 0-500 PSI $\pm 10\%$
 500-1000 PSI $\pm 6\%$
 1000-1500 PSI $\pm 5\%$

CRITICAL DESIGN PT.
 $P_F = 213 \pm 15$ PSI
 $q_c = 12.2$ PSF

CRITICAL DESIGN PT.
 $P_F = 908 \pm 54$ PSI
 $q_c = 37.1$ PSF

FLIGHT TEST DATA







Flight	Symbol
FLIGHT 69	\diamond
FLIGHT 70	∇
FLIGHT 72	\circ

223mm
203mm

1362
875

REGULATED PRESSURE ABOVE RETURN ~ PSI ~ PSF


q_c ~ DYNAMIC AIR PRESSURE ~ PSF



STICK FORCE TO MAINTAIN 1G FLIGHT

PULL
200
180
160
140
120
100
80
60
40
20
0
-20
-40
-60
-80
-100
-120
-140
-160
-180
-200
PUSH

- ◇ -- LEVEL FLIGHT
- ▽ -- DESCENDING FLIGHT
- △ -- CLIMBING FLIGHT
- SOLID SYMBOLS ARE FOR FLAPS 30°




CALC			REVISED	DATE
CHECK				
APR				
APR				
INK	J. JENSEN			

BOOST OFF STICK FORCES
TO MAINTAIN 1G FLIGHT

THE BOEING COMPANY

MOD
C-8A
FGG-2-21
PAGE 114
JAN 1989




NOTE: 1) FORCES SHOWN ARE
DUE TO AERO
LOADS ONLY
2) CURVES BASED ON
FLIGHT TEST RESULTS

CALC			REVISED	DATE
CHECK				
APR				
APR				

CALCULATED
MANUAL REVERSION

THE BOEING COMPANY

MOD
C-8A
FIG 62-22
PAGE 115
10-1-80



CALC			REVISED	DATE
CHECK				
APR				
APR				

STEADY SIDESLIP

THE BOEING COMPANY

MOD
C-BA
FIG. 62-23
PAGE 116
N7-41189

7.0 CONCLUSIONS AND RECOMMENDATIONS

The design, fabrication and testing of a powered elevator system for the Augmentor Wing Jet STOL Research Airplane was successfully conducted within a 12 month time period. The control system was demonstrated by flight test to be airworthy and to meet its design requirements. No adverse system characteristics were noted by the test pilots.

Control problems encountered in the STOL flight regime with the spring tab elevator system have been eliminated by the powered elevator system. Maximum elevator deflection is possible without excessive pilot effort; control feel has been improved; control system response is rapid and precise. This has allowed the pilot to investigate the low speed characteristics of the AWJSRA with greater precision and increased confidence.

The powered elevator has a blowdown speed of 170 knots instead of 100 knots as predicted. The increased elevator deflection capability at high speed could produce excessive tail loads. Because of the relatively low pilot effort required to attain full trailing edge up elevator, the following recommendations are made:

1. Pilots should be cautioned not to make large elevator control inputs above 120 knots. Control forces should be kept below 40 pounds pilot effort.
2. The powered elevator system should be flight tested with the hydraulic supply pressure reduced from its present value of 2440 psi to 1500 psi. This change should be permanently incorporated if system performance is found acceptable.



REFERENCES

1. D6-26057 Longitudinal Control and Airspeed Control System
Study Report
2. D6-40720 The Development of an Augmentor Wing Jet STOL
Research Aircraft (Modified C-8A)
3. D6-40947 Powered Elevator with SAS Provisions - Design Requirement,
Configuration Definition and System Characteristics



APPENDIX A

PILOT FLIGHT REPORT



FLIGHT REPORT

DEL NO AWJSRA	NO. 716	DATE OF TEST 9/19/73
ORDER T-4488	PROJ ENG. Vomaske	PILOT Innis/Grossmith
SHOT NO 69	T.O GROSS WT/C G 44,800#/30.7%	FLIGHT TIME

POSE Flutter Test

Preliminary evaluation of powered elevator.

1. At 90 Kts, A/C seems quite responsive to column inputs. Step attitude changes can be made quickly and precisely. Release from column steps produce 1 or 2 overshoots but are not objectionable because A/C doesn't appear to respond to them and normal pilot activity (hand on wheel) adds sufficient damping to eliminate overshoots. Elevator deflection rate seems satisfactory. Breakout was not noticeable during maneuvering and centering was satisfactory. Force gradient was satisfactory - easily manageable with one hand. With elevator fixed, full nose up and nose down trim produced forces which could be held with one hand. A/C could be controlled with both hands. These same comments would apply up to 120 Kts.
2. Immediately after lift off, aileron forces seemed rather light with some tendency to overcontrol. This didn't bother me after I got used to it, but will have to be evaluated further.
3. Approach to stall was accomplished with flaps 30°, PLF, trim at 90 Kts. One α indicator went off scale (20°) at 66 Kts. The other one was hooked up backwards. Very light buffet was detected at 58 Kts. Stall was at 56 Kts with light buffet, slight nose down pitch and perhaps a little left roll. Recovery seemed to occur with very little α reduction and little or no hysteresis. A/C was quite responsive to forward column input.
4. Landing with flaps 65°, nozzles 70° at 65 Kts. Flare seemed to require more back force than I was used to, but control seemed good. Touchdown was firm but not hard. A/C bounced back in air, however, even with lift dump active. (Throttles were not retarded)

FLIGHT REPORT

L NO C-8A	NO. N716NA	DATE OF TEST 9/21/73
ORDER T-4488	PROJ. ENG. Vomaske	PILOT Grossmith/Innis
IT NO 69	T.O. GROSS WT/C.G. 44,640/30.7	FLIGHT TIME 1.3

OSE

- Item 1 Control sweeps
- Item 2 Take-off $\delta F=25$, 99% N_H , $Noz=6^\circ$ SAS-off.
Precise control of elevator throughout.
- Item 3 10 sec. steady-state. 90 KIAS, $\delta F=30$, 96% N_H , $Noz=6^\circ$ SAS-off.
- Item 4 As per item 3. 80 KIAS SAS-off.
- Item 5 As per item 3. 100 KIAS SAS-off.
- Item 6 110 KIAS. $\delta F=5.6$, PFLF, $Noz=6^\circ$, SAS-off
Elevator and rudder pulses, "B" Hyd. Sys. off.
- Item 7 120 KIAS. as per item 6.
- Item 8 120 KIAS. $\delta F=5.6$, PFLF, $Noz=6^\circ$ SAS-off
Elevator and rudder pulses, both Hyd. Sys. on.
- Item 9 125 KIAS. As per item 8
- Item 10 130 KIAS as per item 8
- Item 12 135 KIAS as per item 8
- Item 13 140 KIAS as per item 8
No peculiarities noted. At 140 KIAS, some longitudinal oscillation noted.
Fuselage bending mode?
- Item 15 100 KIAS. $\delta F=30^\circ$, PFLF, $Noz=6^\circ$ SAS-on.
5 sec. trim shot.
- Item 16 90 KIAS as per item 15
- Item 17 80 KIAS as per item 15

FLIGHT REPORT

- 2 -

L NO 3-76	NO. 711	DATE OF TEST 7-21-73
ORDER	PROJ ENG	PILOT GROSSMITH
T NO. 69	T.O GROSS WT/C G. 44640	FLIGHT TIME

DSE

- Item 18 90 KIAS $\delta F=30^\circ$, Noz= 6° , Flt Path Angle -3° , SAS on
5 sec. trim shot.
- Item 19 90 KIAS as per item 18
- Item 20 100 KIAS as per item 18
- Item 21 60 KIAS, $\delta F=65^\circ$, Noz= 70° , Flt Path Angle $-7\ 1/2^\circ$, 93% N_H sinusoidals,
displacements, full nose up and nose down trim changes, sideslips to 15° ,
pitch attitude changes $+5^\circ$ and $+10^\circ$, approach to stall.
Notes:- in sideslips max. bank angle required for 15° s.s. approximately 5° .
Wanders in yaw.
Approach to stall - 58 KIAS $\alpha = 14^\circ$
53 KIAS $\alpha = 20^\circ$
50 KIAS $\alpha = 24^\circ$
48 KIAS $\alpha = 26^\circ$
At $\alpha = 26^\circ$ some laterally wallowing - lateral control adequate to control.
At approximately $\alpha = 30^\circ$ slight "g" break experienced, no roll-off tendency.
- Item 22 90 KIAS, $\delta F=30^\circ$, Noz= 6° , PFLF.
Pull-up and push overs, 0.4 - 1.6 "g" "A" hyd. sys. off. A slight bump in
the elevator control during the 1.6g maneuver.
- Item 23 As per item 22. with "B" hyd. sys. off.
No bump experienced this time during the 1.6g maneuver.
- Item 25 65 KIAS, $\delta F=65^\circ$, Noz= 70° , 93% N_H - normal approach and landing. Elevator
control precise during the approach, flare and landing forces seemed higher
during flare and landing when compared to original elevator system.

FLIGHT REPORT

DEL NO	NO.	DATE OF TEST
AWISRA	716	9/21/73
B ORDER	PROJ. ENG	PILOT
T-4488	Vomaske	Innis/Grossmith
IGHT NO.	T O. GROSS WT/C G.	FLIGHT TIME
70	46,800#/30.0%	

RPOSE

Powered Elevator Flight Test

1. Approach to stall. Flaps 5.6° , trim at 120 Kts. Terminated at 66 Kts, $\alpha=27^\circ$ where moderate buffet (tail, I think) was encountered. Nose high attitude was quite extreme. Copilot reported 17° up elevator required at min. speed.

Steady state sideslip at 60 KTS, Flaps 65° nozzles 70° , SAS ON. Seemed difficult to stabilize sideslip due to tendency for nose to wander in yaw. SAS doesn't seem to help much. Also noted quite a bit of bottom rudder required in turns.

3. Longitudinal control at 60 Kts. A/C is quite sluggish and quite a bit of opposite control is required to stop pitch rate once established.
4. Approach and landing, 65 Kts. Fairly high back force required to flare A/C but control didn't seem too bad. Landing was OK.

FLIGHT REPORT

MODEL NO AWJSRA	NO 716	DATE OF TEST 9/25/73
OB ORDER T-4488	PROJ. ENG Vomaske	PILOT Innis/Hardy
LIGHT NO 71	T.O. GROSS WT/C.G.	FLIGHT TIME
PURPOSE Powered Elevator Tests		

1. At 160 Kts, Flaps 5.6° - Push over-pull ups. Noticeable increase in buffet as A/C is pushed over to $2^\circ \alpha$. Longitudinal stability and control are excellent. Full nose up and nose down trim can be held with one hand on column.
2. At 120 Kts, no change in longitudinal trim was noticed with $\pm 8^\circ \beta$.
3. Landing approach was made at 60 Kts, $\gamma < 6^\circ$. Flare was more gentle than previous. Control was good.

FLIGHT REPORT

DEL NO C-8A	NO. 716	DATE OF TEST 11/29/73 9/26/73
ORDER	PROJ ENG Vomaske	PILOT Hardy/Innis
HT NO 72	T.O GROSS WT/C.G 46550#	FLIGHT TIME 1:14

POSE

Final Powered Elevator Acceptance Test Flight

This was my first left seat flight with the powered elevator and I was quite pleased with the system. Stick force gradients, breakouts, etc., are very nice from 60-180 kts.

Manual reversion was examined at 90 kts and 30° flaps. Airplane was slightly out of trim ($F_s < 20\%$) when the hydraulics were shut off. No problem maneuvering the aircraft in this mode and feel a successful landing could be made. Large deadband is noticeable but acceptable.

Lateral control was better than on my previous flights (March 73)